



QUAD-PLUG®



PRODUCT ADVANTAGES

- ✓ *STOPS RUNNING WATER IMMEDIATELY*
- ✓ *NON-SHRINK — EXPANDS AS IT SETS*
- ✓ *CONTAINS NO CALCIUM CHLORIDE*
- ✓ *NON-METALLIC*
- ✓ *SULFATE RESISTANT*
- ✓ *EASILY APPLIED*
- ✓ *NO MIXING REQUIRED*

| PART NUMBER | DESCRIPTION |
|-------------|---|
| QUAD-PLUG | Quad Plug® - Hybrid fast acting Cement / #50 Pail |

DESCRIPTION

Quad-Plug® is a blend of special cements and admixtures which are designed to instantly stop running water or seepage in all types of concrete and masonry structures.

APPLICATION INFORMATION

(TO SEAL RUNNING WATER OR LEAKS)

Prepare crack or hole by chipping out loose material to a minimum depth and width of 0.75 in. | 19.05 mm. Using a rubber gloved hand, place a generous amount of dry Quad-Plug to active leak and maintain external pressure for 60 seconds. Repeat until leak stops.

** The values stated in inch-pound units are to be regarded as the standard. The values given in International System are for information only.*

RECOMMENDED FOR

- Sewer Pipes and Manholes
- Concrete Tanks
- Elevator Pits
- Cisterns
- Basements

PHYSICAL PROPERTIES

COMPRESSIVE STRENGTH (ASTM C39):

30 min. >1,500 psi | 10.34 MPa

BOND STRENGTH (ASTM C882):

28 day >500 psi | 3.45 MPa

YIELD: Quad-Plug will yield approximately 0.49 cu. ft. | 0.014 cu. m. per pail.

CEMENTITIOUS



877-450-3701



S1EONLINE.COM



SERVICE@S1EONLINE.COM