



STRUCTURE GUARD®-FM



PRODUCT ADVANTAGES

- ✓ **FAST CURING**
- ✓ **EASY WORKABILITY**
- ✓ **NO MIXING**
- ✓ **FASTER APPLICATION**
- ✓ **SIMPLE SPOT REPAIR**
- ✓ **EXTREME BONDING TO NEARLY ALL SUBSTRATES**
- ✓ **1/4" BUILD CAPABILITY WITH NO SAG**

PART NUMBER	DESCRIPTION
QUAD-SG-FM1.5	Structure Guard® - 1.5 Gallon Kit Epoxy
QUAD-SG-FM6/3	Structure Guard® - 600 x 300 ml Epoxy

DESCRIPTION

Structure Guard®-FM is a 100% solids epoxy mastic used to protect new infrastructure and to rehabilitate existing, damaged, infrastructure. Structure Guard-FM is best applied using a trowel.

APPLICATION INFORMATION

Theoretical Coverage

- Sq. ft. per gallon 250 mils 6.4 sq. ft.
- Sq. ft. per 6 cartridge case 250 mils 9.12 sq. ft.

STORAGE

70°F

POT LIFE

10 minutes at 70°F (21°C)

PHYSICAL PROPERTIES

COLOR: Green

SOLIDS: 100% (no solvents)

VOLATILE ORGANIC COMPOUNDS (VOCs): 0

THICKNESS: 125 to 250 mils per coat

NUMBER OF COMPONENTS: 2

RE-COAT

Must be abraded with the equivalent of 36 grit sand paper after 24 hrs.

SHELF LIFE

24 months unopened

EPOXIES



877-450-3701



S1EONLINE.COM



SERVICE@S1EONLINE.COM