

SilverBack XL



Extended Flexible Couplings

Ideal for Pipe Bursting & Ramming



Benefits

- **Extra Long** for pipe alignment problems
- **Extra Long** to protect against thermal expansion and contraction
- **Extra Long** to secure pipe from unstable ground and structures
- **Extra Long** to resist heavy earth loads

Technical Specs

Gasket

- Manufactured to the requirements of:
 - CSA B602
 - ASTM D 5926
 - ASTM C 1173
- Hardness, Shore "A", Inst. +5..... 65
- Tensile Strength, Min. psi....1000
- Elongation at Rupture, Min. % 250
- Tear Strength, Min 150 in/lb.
- Brittleness Temperature -40°F

316 SS High Torque Clamps

- Gasket torque - 120 in/lb.
- Installation torque to shield - 60 in/lb.

Shear Ring

- Heavy duty shield with high torque clamps
- Steel Gauge - .012"

Coupling

- Manufactured to the requirements of:
 - ASTM C 1173

This product can be custom ordered to fit any common sewer pipe size. Call today to learn more!



Part Number	Description	A		B		C	
		in	mm	in	mm	in	mm
SBXL144	4" Clay to 4" Plastic	5.40	137	4.50	114	10.00	254
SBXL244	4" Plastic to 4" Plastic	4.50	114	4.50	114	10.00	254
SBXL166	6" Clay to 6" Plastic	7.50	191	6.63	168	10.00	254
SBXL266	6" Plastic to 6" Plastic	6.63	168	6.63	168	10.00	254
SBXL188	8" Clay to 8" Plastic	10.00	254	6.63	168	10.00	254
SBXL288	8" Plastic to 8" Plastic	8.63	219	8.63	219	10.00	254
SBXL21010	10" Plastic to 10" Plastic	10.75	273	10.75	273	10.00	254
SBXL21212	12" Plastic to 12" Plastic	12.75	324	12.75	324	10.00	254

The SilverBack XL by S1E is built to be stronger, longer and more durable than any coupling in the market. Useful in ramming or bursting, this product will create greater confidence in your pipe connections.



Your 1 Source for Infrastructure & Water Management Solutions

(810) 412-4740 • www.S1Eonline.com